





中国认可 国际互认 检测 TESTING CNAS L0599

Test Report SL52035272857501TX Date:July 22,2020 Page 1 of 10

HUNAN EEXI TECHNOLOGY&SERVICE CO.,LTD

NO.6, NORTH OF PINGTOU ROAD, LIUYANG HI-TECH INDUSTRIAL DEVELOPMENT ZONE, HUNAN, CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)Particle filtering half mask

Claimed : FFP2

Style No. : YX152

Composition : (A)non-woven fabric, melt-blown fabric, bridge of nose, ear band

Sample Color : (A)WHITE

Manufacturer : HUNAN EEXI TECHNOLOGY&SERVICE CO.,LTD

Test Performed : Selected test(s) as requested by applicant

Sample Receiving Date : Jul 10, 2020

Testing Period : Jul 13, 2020 - Jul 22, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the


sample(s) tested, for further details, please refer to the following page(s).

Conclusion:

| Sample No. | Recommendation Level |
|------------|----------------------|
| (A) | FFP2 NR |

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available or request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerise to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report reter only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or, email: CN.Doccheck@sgs.com



SL52035272857501TX

Date:July 22,2020

Page 2 of 10

Test Result

Personal Protective Equipment - Respiratory Protective Devices- Filtering Half Masks to Protect against Particles- Requirements, Testing, Marking

EN 149:2001+A1:2009

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

| Test Requirement | Results | Comment |
|--|---------|---------|
| Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination before use. | Comply | Pass |

Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

| Test Requirement | Results | Comment |
|---|---------|---------|
| Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used. | Comply | |
| After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps. | Comply | Pass |
| When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse. | Comply | |
| Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer. | Comply | |

Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

| Test Requirement | Results | Comment |
|--|---|---------|
| If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer. With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class. | Not applicable (Not designed to be re-usable) | N.A. |

Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

| Test Requirement | Results | Comment |
|---|------------------|---------|
| The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard. | No imperfections | Pass |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035272857501TX **Test Report**

Clause 7.8 Finish of Parts

Date:July 22,2020 Page 3 of 10

(EN 149:2001+A1:2009, Clause 8.2)

| Test Requirement | Results | Comment |
|---|-------------------------|---------|
| Parts of the device likely to come into contact with the wearer shall have no sharp edges or burrs. | No sharp edges or burrs | Pass |

Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

| Test Requirement | Results | Comment |
|---|-------------------------------|---------|
| The total inward leakage consists of three components: face seal leakage, exhalation value leakage(if exhalation value fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3 and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3 | Detail refer to Appendix 1 | Pass |

Appendix 1: Summarization of Test Data

Inward Leakage Test Data

| Subject | Sample | Condition | Walk(%) | Head | Head | Talk(%) | Walk(%) | Mean(%) |
|---------|--------|-----------|---------|--------------|------------|---------|---------|---------|
| | No. | | | Side/side(%) | up/down(%) | | | |
| Zhou | 1 | A.R. | 5.45 | 6.43 | 6.86 | 7.07 | 4.58 | 6.08 |
| Luo | 2 | A.R. | 7.48 | 5.62 | 8.18 | 6.84 | 7.04 | 7.03 |
| Lu | 3 | A.R. | 6.29 | 6.73 | 5.95 | 5.00 | 6.46 | 6.09 |
| Wang | 4 | A.R. | 4.50 | 5.09 | 5.51 | 5.31 | 5.85 | 5.25 |
| Bao | 5 | A.R. | 7.94 | 5.47 | 7.84 | 6.22 | 7.66 | 7.03 |
| Ding | 6 | T.C. | 7.68 | 5.17 | 4.14 | 6.08 | 5.02 | 5.62 |
| Li | 7 | T.C. | 7.17 | 8.81 | 7.98 | 6.63 | 7.70 | 7.66 |
| Chen | 8 | T.C. | 5.49 | 5.95 | 4.87 | 6.39 | 5.03 | 5.55 |
| Song | 9 | T.C. | 6.56 | 5.94 | 6.38 | 6.59 | 6.18 | 6.33 |
| Ye | 10 | T.C. | 8.62 | 8.04 | 6.87 | 7.31 | 7.30 | 7.63 |

Facial Dimension(mm)

| Subject | Face length | Face Width | Face Depth | Mouth Width |
|---------|-------------|------------|------------|-------------|
| Chen | 125 | 150 | 120 | 58 |
| Lu | 115 | 132 | 107 | 48 |
| Zhou | 115 | 135 | 106 | 52 |
| Li | 125 | 130 | 107 | 46 |
| Luo | 125 | 136 | 100 | 43 |
| Zheng | 128 | 140 | 112 | 55 |
| Wang | 120 | 147 | 103 | 48 |
| Song | 120 | 140 | 100 | 50 |
| Bao | 130 | 134 | 104 | 50 |
| Ding | 134 | 150 | 110 | 52 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



| Test Re | port SL52 | 035272857501TX | Date:July 22,2020 | Page 4 of 10 |
|---------|-----------|----------------|-------------------|--------------|
| Liu | 120 | 135 | 117 | 50 |
| Ye | 126 | 137 | 105 | 52 |

Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

| | | Test Requirement | | Results | Comment | |
|------|-------------|-------------------------------------|-------------------------------------|---------|-----------------|------|
| | | of the filter of the particle filte | the | | | |
| requ | urements of | the following table. | | | | |
| | Classifica | Maximum penetration | Maximum penetration of test aerosol | | | |
| | tion | Sodium chloride test 95 | Paraffin oil test 95 l/min | | | |
| | | l/min | | | Detail refer to | Daga |
| | | % | % | | Appendix 2 | Pass |
| | | max. | max. | | | |
| | FFP1 | 20 | 20 | | | |
| | FFP2 | 6 | 6 | | | |
| | FFP3 | 1 | 1 | | | |

Appendix 2: Summarization of Test Data

Penetration of filter material

| Aerosol | Condition | Sample No. | Penetration (%) |
|----------------------|--|-----------------|--------------------|
| | | 1 | 0.396 |
| | As received | 2 | 0.425 |
| | | 3 | 0.385 |
| | | 4 | 0.402 |
| Sodium chloride test | Simulated wearing treatment | 5 | 0.367 |
| | | 6 | 0.387 |
| | Mechanical strength +Temperature conditioned | 7 | 0.572 |
| | | 8 | 0.602 |
| | Conditioned | 9 | 0.596 |
| | As received | 10 | 0.456 |
| | | 11 | 0.571 |
| | | 12 | 0.508 |
| | | 13 | 0.623 |
| Paraffin oil test | Simulated wearing treatment | 14 | 0.548 |
| | | 15 | 0.492 |
| | Machanian strangeth Tananantuna | 16 | 0.565 |
| | Mechanical strength +Temperature conditioned | 17 | 0.773 |
| | Conditioned | 18 | 0.687 |
| | Flow conditioning : Single fil | ter: 95.0 L/min | |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035272857501TX **Test Report** Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Date:July 22,2020

Page 5 of 10

| Test Requirement | Results | Comment |
|--|---|---------|
| Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health. | No irritation or any other adverse effect to health | Pass |

Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

| Test Requirement | Results | Comment |
|---|-----------------|---------|
| The material used shall not present a danger for the wearer and shall not be of highly flammable nature | Detail refer to | Door |
| When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame. | Appendix 3 | Pass |

Appendix 3: Summarization of Test Data

Flammability

| Condition | Sample No. | Result |
|-------------------------|------------|--------|
| | 1 | NIL |
| As received | 2 | NIL |
| _ | 3 | NIL |
| Temperature conditioned | 4 | NIL |

Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

| Test Requirement | Results | Comment |
|--|-------------------------------|---------|
| The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1,0 % (by volume) | Detail refer to Appendix 4 | Pass |

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

| Condition | Sample No. | Resu | lt(%) |
|--------------|------------|--------|-----------------|
| | | 0.4824 | |
| | 1 | | |
| A a received | | 0.4817 | Maan valuaro 49 |
| As received | 2 | | Mean value:0.48 |
| | | 0.4805 | |
| | 3 | | |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3" Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 f (86-21) 64958763 t (86-21) 61402666

f (86-21) 64958763



SL52035272857501TX **Test Report** Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Date:July 22,2020

Page 6 of 10

| Test Requirement | Results | Comment |
|---|---------|---------|
| The head harness shall be designed so that the particle filtering half mask can be donned and removed easily. | Comply | |
| The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device. | Comply | Pass |

Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

| Test Requirement | Results | Comment |
|--|---------|---------|
| The field of vision is acceptable if determined so in practical performance tests. | Comply | Pass |

Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

| Test Requirement | Results | Comment |
|---|---|---------|
| (a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations. | Not applicable due to No exhalation valve | |
| (b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9. | Not applicable due to No exhalation valve | N.A. |
| (c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s. | Not applicable due to No exhalation valve | |
| (d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s. | Not applicable due to No exhalation valve | |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮編: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035272857501TX

Date:July 22,2020

Page 7 of 10

Clause 7.16 Breathing Resistance

(EN 149:2001+A1:2009, Clause 8.9)

| Test Requirement | | | | | Results | Comment |
|---|----------|----------------------|-------------|--|-----------------|---------|
| The penetration of the filter of the particle filtering half mask shall meet the requirements of the following table. | | | | | | |
| Classification | Maximu | um permitted resista | ance (mbar) | | Detailerterte | Pass |
| | Inf | nalation | Exhalation | | Detail refer to | |
| | 30 l/min | 95 l/min | 160 l/min | | Appendix 5 | |
| FFP1 | 0.6 | 2.1 | 3.0 | | | |
| FFP2 | 0.7 | 2.4 | 3.0 | | | |
| FFP3 | 1.0 | 3.0 | 3.0 | | | |

Appendix 5: Summarization of Test Data

Breathing resistance (mbar)

| | | | | | 1 | | | | | 2 | | | | | 3 | | \neg |
|------------------------|--------------|-------|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--------|
| | Flow rate(l | /min) | Α | В | C | D | Е | Α | В | C | D | Е | Α | В | Č | D | Е |
| As received | Inhalation | 30 | 0.4 | 0.5 | 0.4 | 0.5 | 0.4 | 0.4 | 0.4 | 0.5 | 0.5 | 0.5 | 0.5 | 0.4 | 0.4 | 0.5 | 0.5 |
| | IIIIaiatioii | 95 | 1.9 | 1.9 | 1.9 | 1.8 | 1.9 | 2.0 | 1.9 | 1.8 | 2.0 | 1.8 | 1.9 | 2.0 | 2.0 | 1.8 | 1.9 |
| | Exhalation | 160 | 2.8 | 2.7 | 2.7 | 2.8 | 2.8 | 2.7 | 2.7 | 2.8 | 2.7 | 2.7 | 2.8 | 2.8 | 2.7 | 2.8 | 2.7 |
| | E. ((// :) | | _ 4 5 | | | | | 6 | | | | | | | | | |
| Simulated | Flow rate(l | min) | Α | В | O | ם | Е | Α | В | O | ۵ | Е | Α | В | С | ם | Ε |
| wearing | Inhalation | 30 | 0.5 | 0.4 | 0.5 | 0.5 | 0.4 | 0.4 | 0.5 | 0.5 | 0.4 | 0.5 | 0.4 | 0.4 | 0.5 | 0.5 | 0.4 |
| treatment | IIIIaiatioii | 95 | 1.9 | 2.0 | 1.9 | 1.9 | 1.9 | 2.0 | 2.0 | 1.9 | 1.9 | 2.0 | 2.0 | 1.9 | 1.9 | 2.0 | 1.9 |
| | Exhalation | 160 | 2.7 | 2.8 | 2.7 | 2.7 | 2.8 | 2.8 | 2.7 | 2.7 | 2.8 | 2.8 | 2.7 | 2.7 | 2.7 | 2.8 | 2.7 |
| | [] | /:\ | | 7 8 | | | | 9 | | | | | | | | | |
| | Flow rate(l/ | min) | Α | В | C | D | Е | Α | В | O | ם | Е | Α | В | С | D | Ε |
| Temperature | Inhalation | 30 | 0.3 | 0.4 | 0.3 | 0.4 | 0.3 | 0.3 | 0.4 | 0.3 | 0.3 | 0.4 | 0.3 | 0.4 | 0.3 | 0.3 | 0.4 |
| conditioned Innaiation | 95 | 1.9 | 2.0 | 1.9 | 1.9 | 2.0 | 2.0 | 1.9 | 1.9 | 2.0 | 2.0 | 1.9 | 1.9 | 2.0 | 2.0 | 1.9 | |
| | Exhalation | 160 | 2.8 | 2.7 | 2.7 | 2.8 | 2.7 | 2.7 | 2.8 | 2.7 | 2.8 | 2.7 | 2.8 | 2.7 | 2.7 | 2.8 | 2.7 |

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国·上海·徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035272857501TX

Date:July 22,2020

Page 8 of 10

Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

| | Test Requirement | Results | Comment | |
|---|--|---------------------------------------|---------|--|
| Valved particle fill After clogging the FFP1: 4 mbar, FF The exhalation re flow. Valveless particle After clogging the | eathing resistance tering half masks: e inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb e filtering half masks: e inhalation and exhalation resis FP2: 4 mbar, FFP3: 5 mbar at 95 | Optional for single shift device only | N.A. | |
| Clause 7.17.3 Pe All types (valved | enetration of filter material and valveless) of particle filte grequirement shall also meet th Maximum penetration Sodium chloride test 95 l/min % max. 20 | Optional for single shift device only | N.A. | |
| FFP2 | 6 | 6 | | |
| FFP3 | 1 | 1 | | |

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

| Test Requirement | Results | Comment |
|--|---------|---------|
| All demountable parts (if fitted) shall be readily connected and secured, where possible by hand | Comply | Pass |

| Test | Uncertainty |
|--|-------------|
| Total inward leakage | 3.4% |
| Penetration of filter material | 4.8% |
| Carbon dioxide content of the inhalation air | 3.9% |
| Breathing resistance (30L/min) | 5.9% |
| Breathing resistance (95L/min) | 4.9% |
| Breathing resistance (160L/min) | 4.3% |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rd Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666

t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763




SL52035272857501TX

Date:July 22,2020

Page 9 of 10

Sample Photo





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233

t (86-21) 61402666


t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763



SL52035272857501TX

Date:July 22,2020

Page 10 of 10







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms